



OAK NICE

Oak Nice is a 3-strip floor with moderate colour variations and may contain minor knots.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N19EK50KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Silk lacquer	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	2423 x 200 x 15 mm	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	23 kg	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	2.91 m ²	Collection	European Naturals Collection	Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Area Per Board	0.485 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes medium sound and black knots. Knots may vary in size and numbers.		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m ² K/W)
COLOUR CHANGE		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Some muting of colour variation to medium, straw brown.		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969022477			

CERTIFICATES

